


















## 2MP





PICTURE	MODEL	Main Features	SRP	SDP
	<b>HAC-T1A21N</b>	1/2.7" <b>2Megapixel</b> CMOS 25/30fps@1080P,25/30fps@720P 20m(66ft) IR, Smart IR,ICR, OSD,4in1(CVI/TVI/AHD/CVBS)	950	570
	<b>HAC-B1A21N</b>	1/2.7" <b>2Megapixel</b> CMOS 25/30fps@ <b>1080P</b> ,25/30fps@720P 20m(66ft) IR, Smart IR,ICR, OSD,4in1(CVI/TVI/AHD/CVBS) IP67,Plastic housing	1030	618
	<b>DH-HAC-HDW1200TRQN-0280B-S5</b>	·Max 30fps@1080P ·CVI/CVBS/AHD/TVI switchable · <b>2.8mm</b> fixed lens(3.6mm optional) ·Max. IR length 25m, Smart IR ·IP50, DC12V	1050	630
	<b>DH-HAC-HFW1200CN-0280B-S5</b>	· Max 30fps@1080P · CVI/CVBS/AHD/TVI switchable · <b>2.8mm</b> fixed lens (3.6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V	1160	696
	<b>DH-HAC-HDW1200TRQN-A-0280B-S5</b>	·Max 30fps@1080P ·CVI/CVBS/AHD/TVI switchable · <b>2.8mm</b> fixed lens(3.6mm optional) ·Max. IR length 25m, Smart IR ·IP50, DC12V	1300	858






	<b>DH-HAC-HFW1200CN-A-0280B-S5</b>	<ul style="list-style-type: none"> <li>· Max 30fps@1080P</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· <b>2.8mm</b> fixed lens (2.8mm optional)</li> <li>· Built-in mic</li> <li>· Max. IR length 30m, Smart IR</li> <li>· IP67, DC12V</li> </ul>	1400	918
	<b>DH-HAC-HFW1200CMN-0280B-S5</b>	<ul style="list-style-type: none"> <li>· Max 30fps@1080P</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 2.8mm fixed lens (3.6mm optional)</li> <li>· Max. IR length 30m, Smart IR</li> <li>· IP67, DC12V</li> </ul>	1500	900
	<b>DH-HAC-HFW1200CMN-A-0280B-S5</b>	<ul style="list-style-type: none"> <li>· Max 30fps@1080P</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 3.6mm fixed lens (2.8mm optional)</li> <li>· Built-in mic</li> <li>· Max. IR length 30m, Smart IR</li> <li>· IP67, DC12V</li> </ul>	1700	1020
	<b>DH-HAC-HDW1200TQN-A-0280B-S5</b>	<ul style="list-style-type: none"> <li>· Max 30fps@1080P</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 3.6mm fixed lens (2.8mm, 6mm optional)</li> <li>· Built-in mic</li> <li>· Max. IR length 40m, Smart IR</li> <li>· IP67, DC12V</li> </ul>	1600	1038
	<b>DH-HAC-HDW1200TMQN-A-0360B-S5</b>	<ul style="list-style-type: none"> <li>· Max 30fps@1080P</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 3.6mm fixed lens (2.8mm optional)</li> <li>· Built-in mic</li> <li>· Max. IR length 30m, Smart IR</li> <li>· IP67, DC12V</li> </ul>	2060	1236





	<b>HAC-HDBW1200E-S4</b>	1/2.9" 2Megapixel Exmor CMOS 1080P, ICR, IP67, IK10 Max. IR Led length: 30m, Smart IR 3.6mm fixed lens(2.8mm, 6mm optional)	2000	1284
	<b>HAC-HDBW1200R-Z-S4</b>	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P ICR, OSD, 2.7-12mm motorized vari-focal lens Max. IR distance: 30m(98ft), Smart IR CVI/TVI/AHD/CVBS output switchable DC12V, IP67 & IK10	2500	1944
	<b>HAC-HFW1200D-S4</b>	1/2.7" 2Megapixel CMOS 1080P, ICR, IP67 Max. IR Led length: <b>80m</b> , Smart IR 3.6mm fixed lens(6, 8mm optional)	2000	1320
	<b>DH-HAC-HFW1200RN-Z-IRE6-A</b>	<ul style="list-style-type: none"> <li>· Max 30fps@2MP, 1/2.7" Image sensor</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· <b>2.7~12mm Motorized lens</b></li> <li>· <b>Built-in mic</b></li> <li>· Max. IR length 60m, Smart IR</li> <li>· All Metal</li> <li>· IP67, DC12V</li> </ul>	3770	2262
	<b>HAC-HUM1220A-PIR</b>	1/2.9" 2Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Electronic, OSD, 2.8mm pinhole fixed lens HDCVI/CVBS output switchable DC12V, bulit-in PIR	2440	2136






## FULL COLOR

PICTURE	MODEL	Main Features		SRP	SDP
	<b>DH-HAC-HFW1200CMN-IL-A</b>	<b>2MP Smart Dual Light</b>	<b>Max 25 fps@2MP</b> • <b>Smart Dual Light.</b> • <b>20 m illumination distance.</b> • <b>Super Adapt.</b> • <b>Built-in MIC.</b> • <b>3.6 mm fixed lens (2.8 mm optional).</b> • <b>CVI/CVBS/AHD/TVI switchable.</b> • <b>IP67, 12 VDC.</b>	2500	1500
	<b>DH-HAC-HDW1200TLMN-IL-A</b>			2500	1500
	<b>DH-HAC-HDW1239TLQN-LED</b>	1080P Full-color	1/2.8" 2Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P <b>Full-color Starlight</b>	1500	1320
	<b>DH-HAC-HDW1239TLQN-A-LED</b>	1080P Full-color built-in mic	ICR, OSD, 3.6mm fixed lens(2.8mm optional), <b>20m LED,</b> <b>smart white light</b> <b>CVI/TVI/AHD/CVBS output switchable</b> DC12V, IP67	1700	1440





	<b>HAC-HDW1239T-LED</b>	1080P Full-color	1/2.8" 2Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P <b>Full-color Starlight</b> ICR, OSD, 3.6mm fixed lens, <b>40m LED, smart white light</b> <b>CVI/TVI/AHD/CVBS output switchable</b>	2500	1500
	<b>DH-HAC-HFW1239CN-LED</b>	1080P Full-color	· Max 30fps@2MP, 1/2.8" Image sensor · 24/7 Full-color, Starlight · 130 dB true WDR, Super Adapt · 2.8/3.6mm fixed lens	2300	1380
	<b>DH-HAC-HFW1239CN-A-LED</b>	built-in mic	· Smart warm white light 20m · CVI/TVI/AHD/CVBS switchable · Quick-install design · DC12V, IP67	2500	1500
	<b>HAC-HFW1239T-LED</b>	1080P Full-color	1/2.8" 2Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P <b>Full-color Starlight</b> ICR, OSD, 3.6mm fixed lens, <b>20m LED, smart white light</b> <b>CVI/TVI/AHD/CVBS output switchable</b>	2500	1500
	<b>HAC-HFW1239TLM-LED</b>	1080P Full-color	1/2.8" 2Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P <b>Full-color Starlight</b>	2800	1680
	<b>HAC-HFW1239TLM-A-LED</b>	built-in mic	ICR, OSD, 3.6mm fixed lens, <b>40m LED, smart white light</b> <b>CVI/TVI/AHD/CVBS output switchable</b>	3000	1800
	<b>HAC-HFW1239MHN-LED-0360B</b>	1080P Full-color	24/7 color imaging 50 m illumination distance Max. 30 fps@1080p	3000	1800
	<b>HAC-HFW1239MHN-A-LED-0360B</b>	big case ,built-in mic	CVI/CVBS/AHD/TVI Switchable 3.6mm fixed lens (6mm Optional) IP67, 12V±30% DCFull	3200	1920

	<p><b>DH-HAC-HFW1239TUN-Z-A-LED</b></p>	<p>big case ,built-in mic, motorized lens</p>	<ul style="list-style-type: none"> <li>· Max 30fps@2MP, 1/2.8" Image sensor</li> <li>· 2.7 mm–13.5 mm motorized lens</li> <li>· 24/7 Full-color, Starlight</li> <li>· 130 dB true WDR, Super Adapt</li> <li>· Smart warm white light 60m</li> <li>· Built-in mic</li> <li>· All Metal</li> <li>· CVI/TVI/AHD/CVBS switchable</li> <li>· DC12V, IP67</li> </ul>	<p>5850</p>	<p>3510</p>
	<p>DH-HAC-HFW1500CMN-IL-A</p>	<p><b>5MP Smart Dual Light</b></p>	<p>Max 25 fps@5MP (16:9 video output).</p> <ul style="list-style-type: none"> <li>· Smart Dual Light.</li> <li>· 20 m illumination distance.</li> <li>· Super Adapt.</li> <li>· Built-in MIC.</li> <li>· 3.6 mm fixed lens (2.8 mm optional).</li> <li>· CVI/CVBS/AHD/TVI switchable.</li> <li>· IP67, 12 VDC.</li> </ul>	<p>3000</p>	<p>1920</p>
	<p>DH-HAC-HDW1500TLMN-IL-A</p>			<p>3000</p>	<p>1920</p>
	<p><b>DH-HAC-HDW1509TLQN-A-LED</b></p>	<p>5mp Full-color Starlight</p>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" image sensor</li> <li>· 24/7 Full-color image, Starlight</li> <li>· 16:9 video output</li> <li>· 120 dB true WDR, Super Adapt</li> <li>· Smart warm white light 20m</li> <li>· 2.8/3.6mm fixed lens</li> <li>· Built-in mic</li> <li>· Quick-to-install design</li> </ul>	<p>3250</p>	<p>1950</p>





	<b>DH-HAC-HFW1509TN-LED-0360B</b>	5mp Full-color Starlight	Full-color starlight 20m LED distance Max.20fps@5MP CVI/CVBS/AHD/TVI Switchable 3.6 mm fixed lens IP67, 12V±30% DC	3380	2028
	<b>DH-HAC-HFW1509TLMN-LED-0360B</b>	5mp Full-color Starlight	Full-color starlight 40m LED LED distance Max.20fps@5MP CVI/CVBS/AHD/TVI Switchable 3.6 mm fixed lens IP67, 12V±30% DC	3510	2106
	<b>DH-HAC-HFW1509TLMN-A-LED-0360B</b>	5mp Full-color Starlight	Full-color starlight 40m LED LED distance Max.20fps@5MP CVI/CVBS/AHD/TVI Switchable 3.6 mm fixed lens, Build-in Mic IP67, 12V±30% DC	3640	2184





## 5MP

PICTURE	MODEL	Main Features	SRP	SDP
	<b>DH-HAC-HDW1500TRQN</b>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, <b>Starlight</b></li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· <b>2.8/3.6mm fixed lens</b></li> <li>· Smart IR 25m</li> <li>· Quick Install Design</li> <li>· IP67, DC12V</li> </ul>	1800	1080
	<b>DH-HAC-HFW1500CN</b>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, <b>Starlight</b></li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· <b>2.8/3.6mm fixed lens</b></li> <li>· Smart IR 30m</li> <li>· Quick Install Design</li> <li>· IP67, DC12V</li> </ul>	1920	1152
	<b>DH-HAC-HDW1500TRQN-A</b>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, Starlight</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 2.8/3.6mm fixed lens</li> <li>· Built-in mic</li> <li>· Smart IR 25m</li> <li>· Quick Install Design</li> <li>· IP67, DC12V</li> </ul>	2000	1200
	<b>DH-HAC-HFW1500CN-A</b>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, Starlight</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 2.8/3.6mm fixed lens</li> <li>· Built-in mic</li> <li>· Smart IR 30m</li> <li>· Quick Install Design</li> <li>· IP67, DC12V</li> </ul>	2120	1272










	<p><b>DH-HAC-HFW1500CMN</b></p>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, <b>Starlight</b></li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· <b>2.8/3.6mm fixed lens</b></li> <li>· Smart IR 30m</li> <li>· All Metal</li> <li>· IP67, DC12V</li> </ul>	<p>2360</p>	<p>1416</p>
	<p><b>DH-HAC-HDW1500TLMQN</b></p>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, Starlight</li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 2.8/3.6mm fixed lens</li> <li>· <b>Smart IR 30m</b></li> <li>· <b>Metal Dome &amp; Cover</b></li> <li>· <b>Quick Install Design</b></li> <li>· IP67, DC12V</li> </ul>	<p>2700</p>	<p>1620</p>
	<p><b>DH-HAC-HDW1500TLMQN-A</b></p>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, <b>Starlight</b></li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· <b>2.8/3.6mm fixed lens</b></li> <li>· <b>Built-in mic</b></li> <li>· <b>Smart IR 30m</b></li> <li>· <b>Metal Dome &amp; Cover</b></li> <li>· <b>Quick Install Design</b></li> <li>· IP67, DC12V</li> </ul>	<p>2900</p>	<p>1740</p>
	<p><b>DH-HAC-HFW1500DN</b></p>	<ul style="list-style-type: none"> <li>· Max 25fps@5MP, 1/2.7" Image sensor</li> <li>· 16:9 video output, <b>Starlight</b></li> <li>· CVI/CVBS/AHD/TVI switchable</li> <li>· 3.6/6.0/8.0mm fixed lens</li> <li>· <b>Smart IR 80m</b></li> <li>· <b>All Metal</b></li> <li>· <b>Big HOUSING</b></li> <li>· IP67, DC12V</li> </ul>	<p>3660</p>	<p>2196</p>

	<b>HAC-HFW1500R-Z-IRE6-A</b>	1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P ICR, OSD, 2.7-12mm motorized vari-focal lens Max. IR distance: 60m(197ft), Smart IR CVI/TVI/AHD/CVBS output switchable DC12V, IP67, built-in mic	4810	2886
	<b>HAC-HDW1400EM-A</b>	1/3" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P ICR, OSD, 3.6mm fixed lens(2.8mm, 6mm, 8mm optional) Max. IR distance: 50m(164ft), Smart IR CVI/CVBS output switchable DC12V, IP67, metal	1750	1560







## PTZ





PICTURE	MODEL	Main Features	SRP	SDP
	<b>DH-SD22204DBN-GC</b>	2MP 4x Starlight HDCVI PTZ Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 4x optical zoo > Starlight technology > 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IP66, IK10	10270	6162
	<b>DH-SD42215N-HC-LA</b>	2mp, 15x zoom Alarm:2/1 Audio in:1 · Starlight technology · 120 dB true WDR, 3D DNR · Max. 25/30 fps@1080P, 25/30/50/60 fps@720P · IK10 · IP66	20800	12480
	<b>DH-SD52C232N-HC-LA</b>	32x optical zoom, Starlight, -30°C~60°C wide temperature range, IK10, Max 500 °/s pan speed, 4in1	31590	18954

	<b>DH-SD49225N-HC-LA</b>	<ul style="list-style-type: none"> <li>· 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>· Powerful 25x optical zoom</li> <li>· Starlight technology</li> <li>· 120 dB true WDR, 3D DNR</li> <li>· Max. 25/30 fps@1080P, 25/30/50/60 fps@720P</li> <li>· IP66</li> <li>· IR distance up to 100 m</li> <li>· DC 12V/3A (± 10%)</li> </ul>	22750	13650
	<b>DH-SD59225N-HC-LA</b>	<ul style="list-style-type: none"> <li>· 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>· Powerful 25x optical zoom</li> <li>· Starlight technology</li> <li>· 120 dB true WDR, 3D DNR</li> <li>· Max. 25/30 fps@1080P, 25/30/50/60 fps@720P</li> <li>· IP66</li> <li>· IR distance up to 150 m</li> <li>· DC 24V/3A (±25%)</li> </ul>	26520	15912
	<b>SD59230I-HC</b>	<b>30x</b> optical zoom, <b>Starlight</b> , IR Distance up to 150m, -40°C~70°C wide temperature range, IP66, 4in1		0
	<b>SD6C230I-HC-S3</b>	CA-HAC2030I-S2: 2Mp CMOS, 30x zoom, <b>Starlight</b> , WDR Max 240 °/s pan speed 1ch audio in 2/1ch alarm in/out IP66, -40~60°C		0





# KIT


PICTURE	dahua kit			SRP	SDP
	<b>HDCVI Kit 1080P - 4ch</b>	<b>DH-KIT/XVR1B04/2-B1A21N-0360B/2-T1A21N-0360B</b>	XVR *1, HDCVI Camera *4 Accessory: 18.3m(60ft) BNC&Power Cable *4 Desktop power adapter -AC100V~ 240V/ 12V0. 7A with 1to 4 power splitter *1	<b>6450</b>	<b>5700</b>
	<b>HDCVI Kit 1080P - 8ch</b>	<b>DH-KIT/XVR1B08/4-B1A21N-0360B/4-T1A21N-0360B</b>	XVR *1, HDCVI Camera *8 Accessory: 18.3m(60ft) BNC&Power Cable *8 Desktop power adapter -AC100V~ 240V/ 12V0. 7A with 1to 4 power splitter *2	<b>10900</b>	<b>9500</b>
	<b>HDCVI FULL COLOR Kit 1080P - 4ch</b>	<b>DH-KIT-CVI2MP2B2T-I DH-PH-KIT/XVR1B04-I/2-HFW1239CN-A-LED-0360B/2-HDW1239TLQN-A-LED-0280B</b>	XVR *1, HDCVI Camera *4 Accessory: 18.3m(60ft) BNC&Power Cable *4 Desktop power adapter -AC100V~ 240V/ 12V0. 7A with 1to 4 power splitter *1	<b>14400</b>	<b>8700</b>
	<b>HDCVI FULL COLOR Kit 1080P - 8ch</b>	<b>DH-KIT-CVI2MP4B4T-I DH-PH-KIT/XVR1B08-I/4-HFW1239CN-A-LED-0360B/4-HDW1239TLQN-A-LED-0280B</b>	XVR *1, HDCVI Camera *8 Accessory: 18.3m(60ft) BNC&Power Cable *8 Desktop power adapter -AC100V~ 240V/ 12V0. 7A with 1to 4 power splitter *2	<b>25800</b>	<b>15500</b>


PICTURE	cctv kit		SRP	
 <p><b>1080P COOPER Series 2 PCS CAMERA</b></p>	<p><b>1080P COOPER Series 2 PCS CAMERA</b></p>	<p>DH-KIT 1-XVR1B04 1-HAC-T1A21N 1-HAC-B1A21N</p>	<p>XVR-S2 *1, HD-CVI 2mp Camera *2 Accessory: 10meter siamese Cable *2 12V/1A Power Adapter for Camera *2</p>	<p>3300</p>
 <p><b>1080P COOPER Series 4 PCS CAMERA</b></p>	<p><b>1080P COOPER Series 4 PCS CAMERA</b></p>	<p>DH-KIT 1-XVR1B04 2-HAC-T1A21N 2-HAC-B1A21N</p>	<p>HCVR *1, HD-CVI Camera *4; Accessory: 10meter siamese Cable *2 20meter siamese Cable *2 12V/4A Power Adapter for Camera *1 1 split to 4 power line *1</p>	<p>4950</p>
 <p><b>1080P COOPER Series 6 PCS CAMERA</b></p>	<p><b>1080P COOPER Series 6 PCS CAMERA</b></p>	<p>DH-KIT DH-XVR1A08 3-HAC-T1A21N 3-HAC-B1A21N</p>	<p>HCVR *1, HD-CVI Camera *6; Accessory: 10meter siamese Cable *3 20meter siamese Cable *3 12V/4A Power Adapter for Camera *1 1 split to 4 power line *1 12v 1a 2pcs</p>	<p>7500</p>
 <p><b>1080P COOPER Series 8 PCS CAMERA</b></p>	<p><b>1080P COOPER Series 8 PCS CAMERA</b></p>	<p>DH-KIT DH-XVR1A08 4-HAC-T1A21N 4-HAC-B1A21N</p>	<p>HCVR *1, HD-CVI Camera *8; Accessory: 10meter siamese Cable *4 20meter siamese Cable *4 12V/4A Power Adapter for Camera *2 1 split to 4 power line *2</p>	<p>9000</p>

**1200 series 2mp**

	<b>1080P 2 PCS 1200R CAMERA</b>	DH-KIT XVR4104HS-X1 1-HDW1200RN 1-HFW1200RN	XVR-S2 *1, HD-CVI 2mp Camera *2 Accessory: 18m(60ft) siamese Cable *2 12V/1A Power Adapter for Camera *2		
	<b>1080P 4 PCS 1200R CAMERA</b>	DH-KIT XVR4104HS-X1 2-HDW1200RN 2-HFW1200RN	HCVR *1, HD-CVI Camera *4; Accessory: 18m(60ft) siamese Cable *4 12V/4A Power Adapter for Camera *1 1 split to 4 power line *1		
	<b>1080P 6 PCS 1200R CAMERA</b>	DH-KIT XVR4108HS-X1 3-HDW1200RN 3-HFW1200RN	HCVR *1, HD-CVI Camera *6; Accessory: 18m(60ft) siamese Cable *6 12V/4A Power Adapter for Camera *1 1 split to 4 power line *1 12v 1a 2pcs		
	<b>1080P 8 PCS 1200R CAMERA</b>	DH-KIT XVR4108HS-X1 4-HDW1200RN 4-HFW1200RN	HCVR *1, HD-CVI Camera *8; Accessory: 18m(60ft) siamese Cable *8 12V/4A Power Adapter for Camera *2 1 split to 4 power line *2		

**Full Color**




	<b>2mp 2 PCS 1239 FULL COLOR CAMERA</b>	DH-KIT 1-XVR1B04 3-HDW1239TL-LED 3-HFW1239CN-LED	XVR *1, HD-FULL color 2mp Camera *2 Accessory: 20m siamese Cable *2 12V/1A Power Adapter for Camera *2		4700
---	---	---	---	--	------





	<p align="center"><b>2mp 4 PCS 1239 FULL COLOR CAMERA</b></p>	<p>DH-KIT 1-XVR1B04 3-HDW1239TL-LED 3-HFW1239CN-LED</p>	<p>XVR *1, HD-FULL color 2mp Camera *4 Accessory: 20m siamese Cable *4 12V/4A Power Adapter for Camera *1 1 split to 4 power line *1</p>		<p align="center">7800</p>
	<p align="center"><b>2mp 6 PCS 1239 FULL COLOR CAMERA</b></p>	<p>DH-KIT DH-XVR1A08 3-HDW1239TL-LED 3-HFW1239CN-LED</p>	<p>XVR *1, HD-FULL color 2mp Camera *6 Accessory: 20m siamese Cable *6 12V/4A Power Adapter for Camera *1 1 split to 4 power line *1 12v 1a 2pcs</p>		<p align="center">12000</p>
	<p align="center"><b>2mp 8 PCS 1239 FULL COLOR CAMERA</b></p>	<p>DH-KIT DH-XVR1A08 4-HDW1239TL-LED 4-HFW1239CN-LED</p>	<p>XVR *1, HD-FULL color 2mp Camera *8 Accessory: 20m siamese Cable *8 12V/4A Power Adapter for Camera *2</p>		<p align="center">15000</p>












## XVR



PICTURE	MODEL	Main Features	SRP	SDP
	<b>DH-XVR1B04-I</b>	<ul style="list-style-type: none"> <li>· <b>H.265+/H.265 video compression</b></li> <li>· <b>Supports HDCVI/AHD/TVI/CVBS/IP video inputs</b></li> <li>· <b>4/8/16 channels 1080P Analog Input</b></li> <li>· <b>Supports Full-channel AI-Coding</b></li> <li>· <b>Max 5/10/18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth</b></li> <li>· <b>Up to 4/ 8 channels video stream ( analog channel ) SMD Plus</b></li> <li>· <b>Supports 1 SATA HDD, up to 6 TB</b></li> </ul>	2440	1620
	<b>DH-XVR1B08-I</b>		3920	2352
	<b>DH-XVR1B16-I</b>		7000	4200
	<b>DH-XVR4104HS-I</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· 4 channels 1080P Analog Input</li> <li>· Support 1080N/720P Recording</li> <li>· Supports Full-channel AI-Coding</li> <li>· Max 5 channels IP camera inputs, each channel up to 2MP</li> <li>· Up to 4 channels video stream ( analog channel ) SMD Plus</li> <li>· Supports 1 SATA HDD, up to 6 TB</li> </ul>	2100	1824
	<b>DH-XVR4108HS-I</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 8 channels 1080P Analog Input</li> <li>· Support 1080N/720P Recording</li> <li>· Supports Full-channel AI-Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 10 channels IP camera inputs, each channel up to 6MP</li> <li>· Up to 8 channels video stream ( analog channel ) SMD Plus</li> <li>· Supports 1 SATA HDD, up to 6 TB</li> </ul>	2850	2574

	<b>DH-XVR4116HS-I</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 video compression</li> <li>· 16 channels 1080P Analog Input</li> <li>· Support 1080N/720P Recording</li> <li>· Supports Full-channel AI-Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 18 channels IP camera inputs, each channel up to 6MP</li> <li>· Up to 8 channels video stream ( analog channel ) SMD Plus</li> <li>· Supports 1 SATA HDD, up to 10 TB</li> </ul>	4980	4356
	<b>DH-XVR4216AN-I</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 video compression</li> <li>· 16 channels 1080P Analog Input</li> <li>· Support 1080N/720P Recording</li> <li>· Supports Full-channel AI-Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 18 channels IP camera inputs, each channel up to 6MP</li> <li>· Up to 8 channels video stream ( analog channel ) SMD Plus</li> <li>· Supports 2 SATA HDD, up to 10 TB</li> </ul>	6870	6120
	<b>DH-XVR4232AN-I(V2.0)</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 video compression</li> <li>· 32 channels 1080P Analog Input</li> <li>· Supports Full-channel AI-Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 32 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps Incoming Bandwidth</li> <li>· Long transmission distance over coax cable</li> <li>· Up to 16 channels video stream ( analog channel ) SMD Plus</li> <li>· Supports 2 SATA HDD, up to 16 TB for a single HDD</li> </ul>	18400	11040
	<b>DH-XVR5104HS-I3</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· 4 channels 5MP Analog Input</li> <li>· Support 5M-N/4M-N/1080P/720P Recording</li> <li>· Max 6 channels IP camera inputs, each channel up to 6MP</li> <li>· Up to 1 channel video stream ( analog channel ) Perimeter Protection</li> <li>· Up to 4 channels video stream ( analog channel ) SMD Plus</li> <li>· Up to 1 channel video stream (analog channel ) human face</li> </ul>	2800	2520

	<p><b>DH-XVR5108HS-I3</b></p>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· 8 channels 5MP Analog Input</li> <li>· Support 5M-N/4M-N/1080P/720P Recording</li> <li>· Max 12 channels IP camera inputs, each channel up to 6MP</li> <li>· Up to 1 channel video stream ( analog channel ) Perimeter Protection</li> <li>· Up to 8 channels video stream ( analog channel ) SMD Plus</li> <li>· Up to 1 channel video stream (analog channel ) human face recognition</li> <li>· Supports 1 SATA HDD, up to 10 TB</li> </ul>	<p>4400</p>	<p>3942</p>
	<p><b>DH-XVR5116HS-I3</b></p>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 16 channels 5MP Analog Input</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 24 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth</li> <li>· Up to 2 channel video stream ( analog channel ) Perimeter Protection</li> <li>· Up to 16 channels video stream ( analog channel ) SMD Plus</li> <li>· Up to 2 channel video stream (analog channel ) human face recognition</li> <li>· Supports 1 SATA HDD, up to 16 TB</li> </ul>	<p>11600</p>	<p>6960</p>
	<p><b>DH-XVR5216AN-I3</b></p>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 16 channels 5MP Analog Input</li> <li>· Supports Full-channel AI Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 24 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth</li> <li>· Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>· Up to 16 channels video stream (analog channel) SMD Plus</li> <li>· Up to 2 channels video stream (analog channel) human face recognition</li> <li>· Supports 2 SATA HDD, up to 16 TB for a single HDD</li> </ul>	<p>15600</p>	<p>9360</p>




	<p><b>DH-XVR5232AN-I3</b></p>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 32 channels 5MP Analog Input</li> <li>· Supports Full-channel AI Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 32 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth</li> <li>· Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>· Up to 16 channels video stream (analog channel) SMD Plus</li> <li>· Up to 2 channels video stream (analog channel) human face recognition</li> <li>· Supports 2 SATA HDD, up to 16 TB for a single HDD</li> </ul>	<p>27000</p>	<p>16200</p>
	<p><b>DH-XVR5416L-I3</b></p>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 16/32 channels 5MP Analog Input</li> <li>· Supports Full-channel AI Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> </ul>	<p>33000</p>	<p>19800</p>
	<p><b>DH-XVR5432L-I3</b></p>	<ul style="list-style-type: none"> <li>· Max 32 channels IP camera inputs, each channel up to 8MP; Max 128Mbps incoming bandwidth</li> <li>· Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>· Up to 16 channels video stream (analog channel) SMD Plus</li> </ul>	<p>49000</p>	<p>29400</p>
	<p><b>DH-XVR5432L-I3 / 2pcs 8tb</b></p>	<ul style="list-style-type: none"> <li>· Up to 2 channels video stream (analog channel) human face recognition</li> <li>· Supports 4 SATA HDD, up to 10 TB for a single HDD</li> </ul>	<p>92400</p>	<p>55440</p>
	<p><b>DH-XVR5816S-I3</b></p>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 16/32 channels 5MP Analog Input</li> <li>· Supports Full-channel AI Coding</li> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> </ul>	<p>43000</p>	<p>25800</p>

	<b>DH-XVR5832S-I3</b>	<ul style="list-style-type: none"> <li>· Max 32 channels IP camera inputs, each channel up to 8MP; Max 128Mbps incoming bandwidth</li> <li>· Up to 2 channels video stream (analog channel) Perimeter Protection</li> <li>· Up to 16 channels video stream (analog channel) SMD Plus</li> </ul>	59000	35400
	<b>DH-XVR5832S-I3 2pcs 8tb</b>	<ul style="list-style-type: none"> <li>· Up to 2 channels video stream (analog channel) human face recognition</li> <li>· Supports 8 SATA HDD, up to 10 TB for a single HDD</li> </ul>	102400	61440
	<b>DH-XVR5104HS-4KL-I3</b>	<ul style="list-style-type: none"> <li>· H.265+/H.265 dual-stream video compression</li> <li>· 4/8/16 channels 4K Analog Input</li> <li>· Supports Full-channel AI Coding</li> </ul>	5800	3660
	<b>DH-XVR5108HS-4KL-I3</b>	<ul style="list-style-type: none"> <li>· Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>· Max 16/24 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth</li> </ul>	11000	6600
	<b>DH-XVR5116H-4KL-I3</b>	<ul style="list-style-type: none"> <li>· Up to 2/4 channels video stream (analog channel) Perimeter Protection</li> <li>· Up to 8/16 channels video stream (analog channel) SMD Plus</li> </ul>	22400	13440
	<b>DH-XVR5216AN-4KL-I3</b>	<ul style="list-style-type: none"> <li>· Up to 2/4 channels video stream (analog channel) human face recognition</li> <li>· Supports 1/2 SATA HDD, up to 16 TB for a single HDD</li> </ul>	24700	14820



	<p><b>DH-XVR8816S-4KL-I</b></p>	<p><b>16 Channel Penta-brid 4K 2U Digital Video Recorder</b></p> <ul style="list-style-type: none"> <li>&gt; H.265+/H.265 dual-stream video compression</li> <li>&gt; Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>&gt; Supports 64 channels of IPC access, each channel up to 12MP input; Max 256Mbps incoming bandwidth</li> <li>&gt; HDMI1 4K@60fps output</li> <li>&gt; Up to 16 channel perimeter protection</li> <li>&gt; Up to 4 channel video stream face recognition</li> <li>&gt; Up to 24 face pictures /sec processing</li> <li>&gt; Up to 20 face databases with 100,000 face images in total</li> </ul>		<p>58200</p>
	<p><b>DH-XVR8208A-4K-I</b></p>	<p><b>8 Channel Penta-brid 4K 1U Digital Video Recorder</b></p> <ul style="list-style-type: none"> <li>&gt; H.265+/H.265 dual-stream video compression</li> <li>&gt; Supports HDCVI/AHD/TVI/CVBS/IP video inputs</li> <li>&gt; Supports 64 channels of IPC access, each channel up to 12MP input; Max 256Mbps incoming bandwidth</li> <li>&gt; HDMI1 4K@60fps output</li> <li>&gt; Up to 8 channel perimeter protection</li> <li>&gt; Up to 4 channel video stream face recognition</li> <li>&gt; Up to 24 face pictures /sec processing</li> <li>&gt; Up to 20 face databases with 100,000 face images in total</li> </ul>		<p>48000</p>
	<p><b>DH-XVR8216A-4KL-I</b></p>	<ul style="list-style-type: none"> <li>&gt; Up to 8 channel perimeter protection</li> <li>&gt; Up to 4 channel video stream face recognition</li> <li>&gt; Up to 24 face pictures /sec processing</li> <li>&gt; Up to 20 face databases with 100,000 face images in total</li> </ul>		<p>50400</p>





# FISH EYE

PICTURE	MODEL	Main Features	SRP	SDP
	DH-HAC-EW2501N	1/2.8" 5Megapixel Sony CMOS <b>20fps@5MP, 25/30fps@4MP</b> <b>Starlight</b> , 120dB true WDR ICR, OSD, <b>1.4mm fisheye lens</b> <b>Max. IR distance: 10m(33ft), Smart IR</b> <b>CVI/TVI/AHD/CVBS output switchable</b>	4300	3720
PICTURE	MODEL	Main Features	SRP	SDP
	HAC-HUM1220A-PIR	1/2.9" 2Megapixel Sony CMOS 25/30fps@1080P, 25/30/50/60fps@720P Electronic, OSD, 2.8mm pinhole fixed lens HDCVI/CVBS output switchable DC12V, built-in PIR	2440	2136
	DH-HAC-HUM3201E	1/2.8" 2Megapixel Sony CMOS <b>pinhole camera</b> 25/30fps@1080P, 25/30/50/60fps@720P <b>Starlight</b> , 120dB true WDR Electronic, OSD, 3.6mm pinhole fixed lens(2.8mm optional) CVI/TVI/AHD/CVBS output switchable DC12V	2800	2592



PICTURE	MODEL	Main Features	SRP	SDP
	DH-HAC-ME1239TQN-A-PV	<ul style="list-style-type: none"> <li>&gt; Active deterrence with red blue light, siren and alarm out interface.</li> <li>&gt; Max. 30 fps@1080p.</li> <li>&gt; 130 dB true WDR, 3D NR.</li> <li>&gt; Smart Dual Illuminators.</li> <li>&gt; 40 m illumination distance.</li> <li>&gt; Super Adapt, Built-in MIC.</li> <li>&gt; 3.6 mm fixed lens (2.8 mm optional).</li> <li>&gt; CVI/CVBS/AHD/TVI switchable.</li> <li>&gt; IP67, 12 VDC.</li> <li>&gt; Quick-to-install eyeball saves installation time.</li> </ul>	<b>3780</b>	<b>2268</b>
	DH-HAC-ME1239THN-A-PV	<ul style="list-style-type: none"> <li>&gt; Active deterrence with red blue light, siren and alarm out interface.</li> <li>&gt; Max. 30 fps@1080p.</li> <li>&gt; 130 dB true WDR, 3D NR.</li> <li>&gt; Smart Dual Illuminators.</li> <li>&gt; 40 m illumination distance.</li> <li>&gt; Super Adapt, Built-in MIC.</li> <li>&gt; 3.6 mm fixed lens (2.8 mm optional).</li> <li>&gt; CVI/CVBS/AHD/TVI switchable.</li> <li>&gt; IP67, 12 VDC.</li> </ul>	<b>4180</b>	<b>2508</b>



	<p>DH-HAC-ME1509TQN-A-PV</p>	<ul style="list-style-type: none"> <li>&gt; Max 25 fps@5 MP (16:9 video output).</li> <li>&gt; 120 dB true WDR, 3D NR.</li> <li>&gt; Smart Dual Illuminators.</li> <li>&gt; Protection Against Red-Blue Light Interference.</li> <li>&gt; Active deterrence with red blue light, siren and alarm out interface.</li> <li>&gt; 40 m illumination distance.</li> <li>&gt; Super Adapt.</li> <li>&gt; Built-in MIC.</li> <li>&gt; 3.6 mm fixed lens (2.8 mm optional).</li> <li>&gt; CVI/CVBS/AHD/TVI switchable.</li> <li>&gt; IP67, 12 VDC.</li> </ul>	<p><b>5500</b></p>	<p><b>3300</b></p>
	<p>DH-HAC-ME1509THN-A-PV</p>	<ul style="list-style-type: none"> <li>&gt; Max 25 fps@5 MP (16:9 video output).</li> <li>&gt; 120 dB true WDR, 3D NR.</li> <li>&gt; Smart Dual Illuminators.</li> <li>&gt; Protection Against Red-Blue Light Interference.</li> <li>&gt; Active deterrence with red blue light, siren and alarm out interface.</li> <li>&gt; 40 m illumination distance.</li> <li>&gt; Super Adapt.</li> <li>&gt; Built-in MIC.</li> <li>&gt; 3.6 mm fixed lens (2.8 mm optional).</li> <li>&gt; CVI/CVBS/AHD/TVI switchable.</li> <li>&gt; IP67, 12 VDC.</li> </ul>	<p><b>5900</b></p>	<p><b>3540</b></p>