






















TRANSMISSION






| PICTURE | MODEL | Main Features | | SRP | SDP |
|--|---------------|---------------------------|---|-------------|-------------|
|  | LR1002 | | RJ45 to BNC EoC Passive Converter | | 408 |
|  | PFT1300 | PoE Extender | Interface: 2*RJ45(1 port support PoE) Power supply: 60W Dimension: 79mm*52mm*23mm Weight 0.057kg | | 984 |
|  <small>LR1002-1ET LR1002-1EC</small> | DH-LR1002-1EC | Single-Port EoC Extender | Port: 1*RJ45 10/100Mbps, 1*BNC. Supports RG59 coaxial cable: 400m/100Mbps, 1000m/10Mbps. | 1340 | 1152 |
| | DH-LR1002-1ET | Single-Port EoC Extender | Port: 1*RJ45 10/100Mbps, 1*BNC. Supports RG59 coaxial cable: 400m/100Mbps, 1000m/10Mbps. | 1340 | 1152 |
|  | DH-OTE103T | 1-port Fiber Transmission | Interface: 1xFC, 1x10/100base-T Power supply: DC12V 1A | 2500 | 2304 |
|  | DH-OTE103R | 1-port Fiber Receiver | Interface: 1xFC, 1x10/100base-T Power supply: DC12V 1A | 2500 | 2304 |




| | | | | | |
|---|------------------|--|--|-------------|-------------|
|  | DH-PFM885-I | Elevator Wireless Equipment | Material: Aluminum/ABS Color: White Dimension: 150*150*36mm Weight: 0.5Kg Certification: - | 5800 | 5352 |
| Switch | | | | | |
|  | DH-PFS3005-5ET-L | 5-Port Desktop Fast Ethernet Switch | <ul style="list-style-type: none"> > Compact design: Miniature size and light weight make it easy to deploy > Plug and play: No configuration required > Green technology: Adopts high quality environmentally friendly plastics > 7×24H: Stable performance for long-term operation | 300 | 300 |
|  | DH-PFS3008-8ET-L | 8-Port Desktop Fast Ethernet Switch | | 380 | 360 |
|  | DH-PFS3005-5GT-L | 5-Port Desktop Gigabit Ethernet Switch | <ul style="list-style-type: none"> > Compact design: Miniature size and light weight make it easy to deploy > Plug and play: No configuration required > Green technology: Adopts high quality environmentally friendly plastics > 7×24H: Stable performance for long-term operation | 650 | 636 |
|  | DH-PFS3008-8GT-L | 8-Port Desktop Gigabit Ethernet Switch | | 950 | 948 |
| POE SWITCH | | | | | |

| | | | | | |
|---|-------------------|--|--|-------------|-------------|
|  | DH-PFS3005-4ET-36 | PoE+ 100m | 4 xRJ45 10/100M (PoE) 1 xRJ45 10/100M PoE budget: 36W | 1990 | 1200 |
|  | DH-PFS3006-4ET-36 | PoE+ 250m | 4 xRJ45 10/100M (PoE) 2 xRJ45 10/100M Support PoE watchdog PoE budget: 36W | 2375 | 1500 |
|  | CS4006-4ET-60 | 6-Port Cloud Managed Desktop Switch with 4-Port PoE | <ul style="list-style-type: none"> > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab standards. > Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE power supply standards. > Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE. > A wide operating temperature range and a full metal casing that is fully-enclosed and dust- | 2900 | 1740 |
|  | DH-PFS3006-4ET-60 | 4-port PoE switch(Unmanage d)(Hi-PoE) | <ul style="list-style-type: none"> 4 x10/100M Base-T (PoE power supply) 2 x10/100M Base-T; Port1≤60W, Port2-4≤30W, Total≤60W IEEE802.3af/IEEE802.3at/Hi-PoE Power supply:DC48~57V Dimension: 130mm×85mm×26mm Weight: 259g | 2900 | 1740 |

| | | | | | |
|---|----------------------|------------------------------|--|-------------|-------------|
|  | DH-PFS3010-8ET-65 | 8-port PoE switch(Unmanaged) | 10-Port Fast Ethernet Switch with 8-Port PoE > Support eight 10/100M PoE power supply ports, and two 10/100M uplink ports > Support 802.3af and 802.3at standards > Operating Temperature: -10°C to +55°C > Support 250 m long distance PoE transmission > Support PoE watchdog | 3125 | 2040 |
|  | DH-PFS3010-8ET-96-V2 | PoE+ +. 250m | 8 × RJ-45 10/100 Mbps (PoE) 2 × RJ-45 10/100 Mbps Support PoE watchdog, Intelligent PoE PoE budget: 96W | 4810 | 3180 |
|  | DH-PFS3106-4ET-60 | PoE Switches | 4-Port PoE Switch (Unmanaged) > Layer two Hardened PoE switch > Supports PoE power management > MAC auto learning and aging, MAC address capacity is 8K > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply | 4550 | 2730 |
|  | DH-PFS3110-8ET-96 | PoE Switches | 8-Port PoE Switch (Unmanaged) > Layer two Hardened PoE switch > Supports PoE power management > MAC auto learning and aging, MAC address capacity is 8K > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1-2 supports Hi-PoE 60W power supply | 6500 | 3900 |







| | | | | | |
|---|-----------------|------|---|--------------|--------------|
|  | DH-PFS3218-16ET | 250m | 16 × RJ45 10/100M (PoE) 2 × RJ45 10/100/1000Mbps 2 × SFP 1000 Mbps (combo) Support PoE watchdog, Intelligent PoE PoE budget: 135W | 11700 | 7020 |
|  | DH-PFS3226-24ET | 250m | 24 × RJ45 10/100M (PoE) 2 × RJ45 10/100/1000Mbps 2 × SFP 1000 Mbps (combo) Support PoE watchdog, Intelligent PoE PoE budget: 240W | 14300 | 8580 |
|  | DH-PFS4218-16ET | 250m | Interface: Combo 1000BASE-T/SFP port x 2 10/100 Base-T x16 (Hi-PoE/PoE+/PoE) PoE budget: 190W Dimension: 440mm x300mm x44mm | 10570 | 9060 |
| | DH-PFS4226-24ET | 250m | Interface: Combo 1000BASE-T/SFP port x 2 10/100 Base-T x24 (Hi-PoE/PoE+/PoE) IEEE802.3af/IEEE802.3at/Hi-PoE PoE budget: 240W Dimension: 440mm x300mm x44mm | 12500 | 11112 |




| | | | | | |
|---|---------------------|------|---|--------------|--------------|
|  | DH-PFS3228-24GT-240 | | All-giga Ports 24 × RJ45 10/100/1000 M (PoE) 2 × RJ45 10/100/1000 M 2 × SFP 1000 M Support Intelligent PoE PoE budget: 240W | 22100 | 13260 |
|  | DH-PFS4212-8GT-9 | 250m | All-giga Ports 8 × RJ45 10/100/1000 M (PoE) 2 × RJ45 10/100/1000 M 2 × SFP 1000 M Support PoE watchdog PoE budget: 96W | 13720 | 8232 |
|  | DH-PFS4218-16GT | 250m | All-giga Ports 16 × RJ45 10/100/1000 M (PoE) 2 × RJ45 10/100/1000 M 2 × SFP 1000 Mbps (combo) Support PoE watchdog, Intelligent PoE PoE budget: 130W | 18562 | 11136 |
|  | DH-PFS4218-16GT | 250m | All-giga Ports 16 × RJ45 10/100/1000 M (PoE) 2 × RJ45 10/100/1000 M 2 × SFP 1000 Mbps (combo) Support PoE watchdog, Intelligent PoE PoE budget: 230W | 21600 | 14580 |
|  | DH-PFS4226-24GT | 250m | All-giga Ports 24 × RJ45 10/100/1000 M (PoE) 2 × RJ45 10/100/1000 M 2 × SFP 1000 Mbps (combo) Support PoE watchdog, Intelligent PoE PoE budget: 370W | 30038 | 18000 |

| EPOE SWITCH | | | | | |
|---|--------------------|------------------------------|---|------|-------|
|  | DH-PFL2106-4ET-96 | Long Range 4-port PoE Switch | 1*100/1000 Base-X 1*10/100/1000 Base-T 4*10/100 Base-T(PoE power supply) Port1,2,3≤30W, Port4≤60W, Total≤96W IEEE802.3af, IEEE802.3at, Hi-PoE; transmission distance up to 800m via UTP ; | 5000 | 4860 |
|  | LR2110-8ET-120 | 8-port ePoE Switch | L2 Managed ePoE Switch 1x100/1000 Base-X 1x10/100/1000 Base-T 8x10/100 Base-T(8 ePoE) Port1,5≤60W, Others≤30W, Total≤120W IEEE802.3af, IEEE802.3at, Hi-PoE transmission distance up to 800m via UTP | | 6588 |
|  | DH-LR2218-16ET-240 | 16-port ePoE Switch | L2 Managed ePoE Switch 2x1000 Combo; 16x10/100 Base-T(8 ePoE+8 PoE) Port1,2≤60W, Others≤30W, Total≤240W IEEE802.3af, IEEE802.3at, Hi-PoE transmission distance up to 800m via UTP | | 11520 |







JUNCTION BOX






| PICTURE | MODEL | Main Features | SRP | SDP |
|---|-------------|--------------------|--|-----|
|  | DH-PFA134 | Junction Box | Basic water-proof Perfect matched for IR Bullet Cameras .HFWxxS,HFWxxR ,HFWxxT,hfw1200rn,ipc-hfw1230sn | 240 |
|  | DH-PFA135 | Junction Box | Basic water-proof Perfect matched for HFWxxxRE-Z, HFW xxRN-VF-Z,HFWxxBN,HFWxxDN, | 216 |
|  | DH-PFA136 | Junction Box | Basic water-proof Perfect matched for HDBWxxE-Z, EB ,HDWxxS series Security Camera | 240 |
|  | DH-PFA137 | Junction Box | for HDBWXXR, HDWXXR-Z, SD22 Series | 240 |
|  | DH-PFA130-E | Junction Box | IP66, IK10 For HFW xxRN-VF-Z,HFWxxBN,HFWxxDN,HFWxxTN bullet, HDWxxR -Z,HDWxxS,HDWxxT-Z-A Series ,HDWxxEM,HDWxxT,HDWxxR Series,eyeball | 420 |
|  | DH-PFA120 | Wall Mount Bracket | Basic water-proof For PTZ camera | 480 |

| | | | | |
|---|-------------|--------------------|--|-----|
|  | DH-PFB204W | Wall Mount Bracket | Basic water-proof Rapid installation For 4 screws to fix | 396 |
|  | DH-PFA150 | | | 756 |
|  | DH-PFA152-E | | | 462 |
| | 8018 | | | 0 |






| PICTURE | MODEL | Main Features | SRP | SDP |
|---|-------------------|---|------|------|
|  | DH-PFM920I-5EUN | 305m Cat5e UTP 0.45 OFC+PVC+Flame retardant 99.99% ofc(oxygen free copper) excellen material | 4800 | 3840 |
|  | DH-PFM920I-6UN1-C | 305m Cat6 UTP 0.52 mm ± 0.02 mm OFC+PVC+Flame retardant UL CM | 6000 | 4920 |
|  | DH-PFM920I-6UN-CN | 305m Cat6 UTP 0.53 OFC+PVC+Flame retardant UL CM | 6600 | 5280 |
|  | DH-PFM920I-6U-C | 305m Cat6 UTP 0.57 OFC+PVC+Flame retardant CPR Eclass 99.99% ofc(oxygen free copper) excellen material | 7950 | 6360 |



| PICTURE | MODEL | Main Features | | SRP | SDP |
|---|-------------|-------------------------------------|--|-------|-------|
|  | DH-PFM900-E | tester | Material: PC Color: yellow/gray Dimension: 190*113*37mm Weight: 0.5Kg | | 20880 |
|  | DH-PFM905-E | tester | Material: PC Color: yellow/gray Dimension: 175*113*37mm Weight: 0.38Kg Certification: CE/FCC | 11000 | 10440 |
|  | DH-PFM820 | UTC | Material: PC&ABS Color: White Dimension: 90*41*21mm Weight: 48g Certification: - | 600 | 480 |
|  | DH-OTC102T | 1ch HDCVI Optical Transceiver | Interface: 1xFC, 1xBNC Power supply: DC12V 1A Dimension: 104.6×96.2×29.5mm Weight: 0.2Kg | 3200 | 3120 |
|  | DH-OTC102R | | Interface: 1xFC, 1xBNC Power supply: DC12V 1A Dimension: 104.6×96.2×29.5mm Weight: 0.2Kg | 3200 | 3120 |





| | | | | | |
|---|----------------------------|--|---|-------|------|
|  | DH-PFO2410T | 4ch HDCVI Optical Transceiver (Lite) | Interface: FC、4*BNC、1*RS485 Power supply: DC12V 1A Dimension:100mm×150mm×30mm Weight: 480g | 4500 | 4200 |
|  | DH-PFO2410R | | Interface: FC、4*BNC、1*RS485 Power supply: DC12V 1A Dimension:100mm×150mm×30mm Weight: 480g | 4500 | 4200 |
|  | DH-PFO2810T | 8ch HDCVI Optical Transceiver(Lite) | Interface: FC、8*BNC、1*RS485 Power supply: DC12V 1A Dimension:100mm×150mm×42mm Weight: 630g | 10000 | 9360 |
|  | DH-PFO2810R | | Interface: FC、8*BNC、1*RS485 Power supply: DC12V 1A Dimension:100mm×150mm×42mm Weight: 630g | 10000 | 9360 |
|  | NKB1000/KBD1000/K B1000 | Display & Control | NKB1000/KBD1000/KB1000 Network Keyboard & Control Keyboard & Dome keyboard | | 9000 |






| | | | | | |
|---|-----------------------------------|------------------------------|--|--|--------------|
|  | <p>NKB5000(-F)</p> | <p>Display & Control</p> | <ul style="list-style-type: none"> > Keyboard to control -DAHUA Standalone DVR -DAHUA high speed dome -Central Management Platform -Network Video Server > RS232, RS485 & network connections (WLAN) > Four dimensional joystick control of PTZ functions > Support 4K decoding live view > Support 4CH HDMI output > Support snapshot and recording to U-disk > Support Video-Wall display control > Preset Position Auto Scan Auto Pan Auto Tour | | <p>54600</p> |
|  | <p>DHI-NVD0405DH-2I-4K</p> | <p>Display & Control</p> | <p>Ultra-HD Network Video Decoder</p> <ul style="list-style-type: none"> > H.265/H.264/MPEG4 video decoding > 4ch@12M/4ch@4K/16ch@1080P/64ch@D1 decoding ability > 1ch HDMI input, 4ch HDMI/VGA/BNC output, HDMI support Ultra HD 4K output > Support up to 4 video-wall display units > Support audio, alarm, bi-directional talk, RS485 | | |



| | | | | | |
|---|----------------------------|-------------------|---|--|--|
|  | DHI-NVD0905DH-4I-4K | Display & Control | Ultra HD Network Video Decoder > Designed for standalone operator viewers > H.265+/H.265/H.264/MJPEG/MPEG4/MPEG2 video decoding > Ultra-high decoding ability, up to 32MP > 2ch HDMI and 2ch DVI-I input, 9ch HDMI output > Supports 1/4/6/8/9/16/25/36 and free split > Supports alarm, RS232, RS485 | | |
| | DHI-M70-4U-E | Display & Control | | | |
| | VDC0605H-M70 | Display & Control | | | |
| | VEC0404HH-M70 | Display & Control | | | |



TV MONITOR



| PICTURE | MODEL | Main Features | | SRP | SDP |
|---|-----------------|--|---|------|------|
|  | DHI-LM19-A202 | LED Monitor | <ul style="list-style-type: none"> > Light and cost-effective plastic housing > High fidelity digital processing for a brilliant and vivid video > 5ms fast response time with no image blurring or ghosting > Low energy consumption, long service life | | |
|  | DHI-LTV24-LN100 | HD, ATV | <ul style="list-style-type: none"> > Abundant interfaces including HDMI, VGA, audio out, USB, AV-in > Supports PAL, NTSC, SECAM ATV system > Supports picture, audio, video and multimedia playing > Supports multiple languages, picture modes and sound | | 4920 |
|  | DHI-LTV32-LN100 | HD, ATV | <ul style="list-style-type: none"> > Abundant interfaces including HDMI, VGA, audio out, USB, AV-in > Supports PAL, NTSC, SECAM ATV system > Supports picture, audio, video and multimedia playing > Supports multiple languages, picture modes and sound modes > High cost performance and low power consumption | 7700 | 5820 |
|  | DHI-LTV32-SD100 | 32" HD Android TV Original Google system | <ul style="list-style-type: none"> > 178°H/178°V extra-wide viewing angle for overall viewing performance > Support the adjustment of brightness, contrast, color and definition of the display > Support multiple signal inputs > Professional thermal design to extend equipment lifespan | | 7560 |





| | | | | | |
|---|-----------------|--|--|-------|-------|
|  | DHI-LTV43-SN200 | FHD, Smart ATV | <ul style="list-style-type: none"> > Abundant interfaces including HDMI, VGA, audio in/out, USB, AV-in, YPbPr > Supports PAL, NTSC, SECAM ATV system > Supports picture, audio, video and multimedia playing > Supports multiple languages, picture modes and sound modes | 12000 | 11400 |
|  | DHI-LTV43-SD200 | FHD, Android TV Original Google system | <ul style="list-style-type: none"> > 178°H/178°V extra-wide viewing angle for overall viewing performance > Support the adjustment of brightness, contrast, color and definition of the display > 8ms fast response time with no image blurring or ghosting > Support multiple signal inputs | | 12600 |
|  | DHI-LTV43-SD400 | UHD (4K), Android TV Original Google system | <ul style="list-style-type: none"> > 178°H/178°V extra-wide viewing angle for overall viewing performance > Support the adjustment of brightness, contrast, color and definition of the display > 9ms fast response time with no image blurring or ghosting > Support multiple signal inputs | | 14400 |
|  | DHI-LTV55-SD400 | UHD (4K), Android TV Original Google system | <ul style="list-style-type: none"> > Ultra-thin bezel design > 178°H/178°V extra-wide viewing angle for overall viewing performance > High fidelity digital processing for a brilliant and vivid video > Support the adjustment of brightness, contrast, color and definition of the display | 26000 | 21600 |
|  | DHI-LTV65-SD400 | UHD (4K), Android TV Original Google system | <ul style="list-style-type: none"> > Ultra-thin bezel design > 178°H/178°V extra-wide viewing angle for overall viewing performance > High fidelity digital processing for a brilliant and vivid video > Support the adjustment of brightness, contrast, color and definition of the display | 26000 | 29760 |



| | | | | | |
|---|-----------------|----------------------|--|--|-------|
|  | DHI-LTV65-SN400 | UHD (4K) Smart TV | <ul style="list-style-type: none"> > Ultra-thin bezel design > 178°H/178°V extra-wide viewing angle for overall viewing performance > High fidelity digital processing for a brilliant and vivid video > Support the adjustment of brightness, contrast, color and definition of the display | | 27000 |
|  | DHI-LTV75-SN400 | UHD (4K) Smart TV | <ul style="list-style-type: none"> > 8ms fast response time with no image blurring or ghosting > Support multiple signal inputs > Professional thermal design to extend equipment lifespan | | 39000 |



VIDEO INTERCOM

| PICTURE | MODEL | Main Features | SRP | SDP |
|---|----------------|--|-----|-------|
|  | DHI-KTP01L (F) | <ul style="list-style-type: none"> · Anodized aluminum front panel · CMOS low illumination 2MP HD colorful 140° camera · Video intercom function · Access control function that supports two locks · Use the app to talk to visitors or unlock the door remotely on your phone. · Surface mounted and flush mounted. · PoE · IK07&IP65 <p>IP Indoor Monitor</p> <ul style="list-style-type: none"> · 7" TFT capacitive touch screen · 6-channel alarm input and 1-channel alarm output · Supports standard PoE · SOS alarm · Supports daisy chain topology <p>Switch</p> <ul style="list-style-type: none"> · Port1-4: 4 × RJ-45 10/100 M (PoE) Port 5: 1 × RJ-45 10/100 M (uplink) · Supports guide rail mount. | | 15540 |
|  | DHI-KTA02 | <ul style="list-style-type: none"> > 7" TFT screen > Video intercom function: Unlock, voice call, video call, volume adjustment > System Capacity: 2 door stations + 3 indoor monitors > Multiple bell sounds > Supports digital wide dynamic range (DWDR) | | 4452 |

| | | | | |
|--|----------------|---|--|-------|
|  | DHI-KTA02M | <ul style="list-style-type: none"> · 7" TFT screen · Video intercom function: Unlock, voice call, video call, volume adjustment, doorway monitoring · System Capacity: 2 door stations + 3 indoor monitors · Multiple bell sounds | | 4620 |
|  | DHI-KTW02 | <p>Wi-Fi Villa Door Station</p> <ul style="list-style-type: none"> · Ultra slim design · PC and ABS material make it ideal for indoor and outdoor use · 1/2.8" 2-MP HD CMOS camera · Offers two-way video call with indoor monitors | | 10500 |
|  | DHI-ASA1222E | <p>Dahua Fingerprint, Password Attendance Standalone</p> <ul style="list-style-type: none"> > Built with 16 mechanical buttons, a 2.4 inch LCD display and has a user friendly interface. > Personnel can clock in and out with fingerprint, password and others. > Supports up to 1,000 users, 2,000 fingerprints, 1,000 | | 2856 |
|  | DHI-ASA1222E-S | <ul style="list-style-type: none"> · TCP/IP based · External electronic bell · 2.4 inches TFT colorful screen · Extremely speed verification · Multiple verification methods (FP/PWD, only FP, only PWD) | | 3360 |

| | | | | |
|--|------------------------|---|--|--------------|
|  <p>The image shows a square-shaped facial recognition device with a black frame. The screen displays a face being scanned. Above the screen is a 'FACE' icon. The Hikvision logo is visible at the bottom of the device.</p> | <p>DHI-ASI3213A-W</p> | <ul style="list-style-type: none"> • 2-MP wide-angle dual-lens camera with IR illumination and DWDR. • Multiple unlock methods including face and password. You can also combine them to create your own personal unlock methods. • Supports mask detection. • Supports visitor QR code with DSS Pro Platform. • Recognizes faces 0.3 m to 1.5 m away (0.98 ft-4.92 ft). • Supports 3,000 users, 3,000 faces, 3,000 passwords, 5,000 cards, 50 administrators, and 300,000 records. • Liveness detection has a face recognition accuracy rate of 99.9% and | | <p>6300</p> |
|  <p>The image shows a vertical rectangular facial recognition device with a black frame. The screen displays a face being scanned. The Hikvision logo is visible at the bottom of the device.</p> | <p>DHI-ASI6213J-MW</p> | <ul style="list-style-type: none"> • 4.3-inch LCD touch screen; resolution 480 × 272 • 2MP wide-angle dual lens camera; support DWDR, white light fill light and IR fill light • Support face, card, password unlock and unlock through their combinations; support unlock by period • User data can be stored at the access controller; can hold 6000 face images and work without network • Face-camera distance: 0.3 m-1.5 m | | <p>14280</p> |